

L.B.WHITE**PREMIER® HEATERS**
DUCTABLE • ENCLOSED FLAMED • DIRECT-FIRED

PREMIER®	40	80	80 DF	170	170 DF	350 DF
BTU/H RATING	40,000	80,000	80,000	170,000	170,000	350,000
HEATED AIR OUTPUT (CFM)	330	450	450	1,200	1,200	2,500
FUEL TYPE	LP	LP	LP, NG	LP	LP, NG	LP, NG
FUEL CONSUMPTION LP GAS MAX (LBS./HR.)	1.86	3.7	3.7	7.9	7.9	16.2
FUEL CONSUMPTION NAT. GAS MAX (CU.FT./HR.)	-	-	80	-	170	350
AMPS (STARTING/CONTINUOUS OPERATION)	2.6 / 1.0	5.0 / 1.5	5.0 / 1.5	7.3 / 5.0	7.3 / 5.0	25.0 / 9.0
AMPS (STANDARD 15 AMP CIRCUIT)	YES	YES	YES	YES	YES	YES*
MOTOR HORSEPOWER	1/12	1/8	1/8	1/3	1/3	1
LENGTH (IN.)	24.8	28	28	32.3	32.3	48.3
WIDTH (IN.)	14.5	13.5	13.5	24.3	24.3	28.0
HEIGHT (IN.)	16.2	22.75	22.75	32.0	32.0	41.0
SHIPPING WEIGHT (LBS.)	60	79.0	79.0	161.0	161.0	320.0
FAN ONLY MODE	S	S	S	S	S	S
TRI-SHIELD COATED CASE**	S	S	S	S	S	S
WHEELS	-	-	-	S	S	S
GAS PRESSURE REGULATOR (W/POL)	S	S	S	S	S	S
THERMOSTAT (WEATHERPROOF W/ 1.4' CORD)	S	S	S	S	S	S W/ 25' CORD
GAS HOSE	15'	15'	15'	15'	15'	15'
DUCTING (W/ MAGNETIC DUCT ADAPTER)	8" X 12" LONG- 132544	12" DIA. X 12' LONG- 26346	12" DIA. X 12' LONG- 26346	12" DIA. X 12' LONG- 26346	12" DIA. X 12' LONG- 26346	18" DIA. X 12" LONG-24442
CERTIFIED TO ANSI/CSA STANDARDS	YES	YES	YES	YES	YES	YES

TWO YEAR WARRANTY

S=Standard

*Amps spike over 15 during initial start-up. Check breaker capability

** Tri-shield coating consists of 3 unique protective layers including: a non-corrosive hot-dipped galvanized steel, an oven-cured epoxy primer and baked, thermosetting polyester.

*** Ducts are optional. Part numbers listed. Duct part numbers can differ for previously built models. Please call L.B. White for specific part numbers.

CA RESIDENTS:

Cancer and reproductive harm. See
www.P65Warnings.ca.gov.**INNOVATIVE HEATING SOLUTIONS**411 Mason Street, Onalaska, WI 54650
(800) 345 7200
(608) 783 5691
(608) 783 6115, fax
www.lbwhite.com© 2019 L.B. White Co.
All rights reserved.
All specifications are subject
to change without notice.